



CONSTRUCTION NOTES

1. ALL WIRES SHALL BE 22 AWG TEFZEL COATED
2. TWISTED WIRES SHALL HAVE 8-10 TWIST'S PER INCH
3. HEATSHRINK SHALL BE USED TO TERMINATE THE SNAKESKIN AT THE BASE OF EACH DSUB CONNECTOR
4. TIE SHEILDS TOGETHER AND TERMINATE AT THE INTERCOM MASTER GND (PIN #1)
5. TIE SHEILDS TOGETHER AND TERMINATE AT INTERCOM GROUND

AFS Control Module

INTERCOM/AUDIO PNL DSUB-25

CONNECTOR - 50,125M
BACKSHELL - 50,125S
PINS - 50,100M

NOTE #5

ITEM	QTY	PART #	DESCRIPTION
NOTES:			
PHONE: (503) 263-0037 FAX: (503) 263-1138 320 REDWOOD ST CANBY, OR 97013			
DATE	8/7/19	SCALE	NONE
DRN	XX	APRV	XX
This drawing is the property of Advanced Flight Systems Inc. and contains confidential information. It is not to be copied, reproduced or used without written approval.			TITLE PM3000 Intercom to ACM
REV	DATE	DESCRIPTION	REV BY
2	8/8/19	Reorganized Grounds and Corrected Pilot Mic Label	SR
1	8/7/19	Added Template to Pre-existing Drawing	SR
P/N	57602	A	1