



CONSTRUCTION NOTES

1. ALL WIRES SHALL BE 22 AWG TEFLON COATED
2. TWISTED WIRES SHALL HAVE 8-10 TWIST'S PER INCH
3. HEATSHRINK SHALL BE USED TO TERMINATE THE SNAKESKIN AT THE BASE OF EACH DSUB CONNECTOR

SYMBOL KEY



| REV | DATE | DESCRIPTION | REV BY |
|-----|--------|-----------------|--------|
| 2 | 3/8/19 | Initial Drawing | RJH |
| 1 | 3/8/19 | Initial Drawing | IRB |

| ITEM | QTY | PART # | DESCRIPTION |
|---|--------|--------|-------------|
| NOTES: | | | |
| <p>ADVANCED FLIGHT SYSTEMS INC. PHONE: (503) 263-0037 FAX: (503) 263-1138 320 REDWOOD ST CANBY, OR 97013</p> | | | |
| DATE | 3/8/19 | SCALE | NONE |
| DRN | RJH | APPV | RJH |
| <small>This drawing is the property of Advanced Flight Systems Inc. and contains confidential information. It is not to be copied, reproduced or used without written approval.</small> | | | |
| TITLE AF-5000, GH5, CO, Ether | | | P/N 57305 |
| ACM Backup Harness | | | B 3 |