


**BACKUP BATTERY CONNECTOR**



**AFS Control Module**

BACKUP BATT DSUB-9

CONNECTOR - 50,109F  
BACKSHELL - 50,109S  
PINS - 50,100F


**CONSTRUCTION NOTES**

1. ALL WIRES SHALL BE 22 AWG TEFLON COATED
2. TWISTED WIRES SHALL HAVE 8-10 TWIST'S PER INCH
3. HEATSHRINK SHALL BE USED TO TERMINATE THE SNAKESKIN AT THE BASE OF EACH DSUB CONNECTOR

**SYMBOL KEY**



**BACKUP BATTERY CONNECTOR**



	LENGTH (IN)
	X
RV-7	38"
RV-8	38"
RV-10 AEROSPORT	38"
RV-10	38"
RV-14	36"
SPORTSMAN	36"

REV	DATE	DESCRIPTION	REV BY
4	2/12/20	Added Length Table	SR
1	6/18/14	Initial Drawing	IRB

ITEM	QTY	PART #	DESCRIPTION
NOTES:			
<p><b>ADVANCED FLIGHT SYSTEMS INC.</b></p> <p>PHONE: (503) 263-0037 FAX: (503) 263-1138 320 REDWOOD ST CANBY, OR 97013</p>			
DATE 12/12/18		SCALE NONE	
DRN: RJH		APPV: RJH	
<p>This drawing is the property of Advanced Flight Systems Inc. and contains confidential information. It is not to be copied, reproduced or used without written approval.</p>			
TITLE Skyview Backup Battery Harness			P/N 57265
			REV. 5